

ORBITAL SHAKER SHA5E-070



ORBITAL SHAKER SHA5E-070

Allows for easy and accurate rack placement, data retrieval on power failure and slow start up function prevents liquid spillage. Applications like stability and dissolution studies, liquid extractions, protein precipitation studies, small peptide synthesis and dilutions makes it an ideal choice.

Used in Stability, Dissolution Studies, Liquid Extractions, Protein Precipitation, Small Peptide Synthesis, Dilutions.
Also known as Laboratory Orbital Shaker.

SHA5E-070 ORBITAL SHAKER

Three-dimensional rocking motion

Max. load capacity is 5kg with platform

Double LCDs for independent display of time and speed

Various platform accessories are available

DC Motor



SPECIFICATIONS

Model	SHA5E-070
Speed Range	10-70 rpm
Timing Range	1 min-19 h 59 min
Motion	Reciprocal
Angle Range	9°
Motor rating Input [W]	40
Motor rating output [W]	24
Maximum Load Capacity	5 kg
Overall Dimension	360x430x106 mm
Display	LCD
Weight	9 kg
Fuse	250 V,1 A, Φ 5x20
Power	50 W
Power Supply	100-240 V, 50/60 Hz

OPTIONAL ACCESSORIES

Accessory Code	Name
1901711005	Universal attachment black
1901709006	Fixing clip for flask volume 25 ml
1901709007	Fixing clip for flask volume 50 ml
1901709008	Fixing clip for flask volume 100 ml
1901709009	Fixing clip for flask volume 200 / 250 ml

Accessory Code	Name
1901709010	Fixing clip for flask volume 500 ml
1901711006	Fixing clip attachment
1901711007	Dish platform with non-slip mat and fixed string(8 pcs)
1901711008	Universal attachment with 4 bars

1901711009

Lengthways roller attachment

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@mail.labstac.com | Website: labstac.com