

ORBITAL SHAKER SHA5G-080



ORBITAL SHAKER SHA5G-080

Allows for easy and accurate rack placement, data retrieval on power failure and slow start up function prevents liquid spillage. Applications like stability and dissolution studies, liquid extractions, protein precipitation studies, small peptide synthesis and dilutions makes it an ideal choice.

Used in Stability, Dissolution Studies, Liquid Extractions, Protein Precipitation, Small Peptide Synthesis, Dilutions.
Also known as Laboratory Orbital Shaker.

SHA5G-080 ORBITAL SHAKER

Three-dimensional rocking motion

Max. load capacity is 3kg with platform

Various platform accessories are available

DC Motor

SPECIFICATIONS

Model	SHA5G-080
Speed Range	0-80 rpm
Permissible Ambient Temperature	5-40°C, 80%RH
Angle Range	7°
Motor rating Input [W]	16
Motor rating output [W]	10
Maximum Load Capacity	3 kg
Overall Dimension	270x330x130 mm
Weight	2.7 kg
Power	20 W
Power Supply	100-240 V,50/60 Hz

OPTIONAL ACCESSORIES

Accessory Code	Name
1901709005	Universal attachment black
1901709006	Fixing clip for flask volume 25 ml
1901709007	Fixing clip for flask volume 50 ml
1901709008	Fixing clip for flask volume 100 ml
1901709009	Fixing clip for flask volume 200 / 250 ml

Accessory Code	Name
1901709010	Fixing clip for flask volume 500 ml
1901709011	Fixing clip attachment
1901709012	Dish Attachment with non-slip mat
1901709013	Universal attachment with 3 bars
1901709014	Lengthways roller attachment

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com