

ROCKING SHAKER SHA63-80C



ROCKING SHAKER SHA63-80C

Rocking Shaker are designed to deliver salient performance, accuracy, and reproducible results for all your application needs. Lightweight and portable for easy transfer, outstanding uniform motion, high quality stain resistant platforms with non-slip rubber mats and low noise are the efficient and reliable features that makes it unique.

Used in Laboratory, Research, Mixing, Incubation.

Also known as Laboratory Rocking Shaker.

SHA63-80C ROCKING SHAKER

Platform made of stainless steel and natural rubber, which is alkali-resistance, non-deformation, easy-clean and spill-prevention

Speed real-time display and diminishing time display

The bearing is articulaed rotating, secure and no wear, suitable for long time use

Compact designed, take very little space

Brushless DC motor, free maintenance

SPECIFICATIONS

Model	SHA63-80C
Speed Range	5-80 rpm
Swing Cycloid	25 mm(Up and Down) / 10°
Timing Range	1 min~99 h 59 min
Maximum Load Capacity	5 kg(double-deck platform)
Platform Dimension	L.280 x W.228 mm
Overall Dimension	284x264x134 mm
Weight	6.0 kg
Fuse	250 V,1 A, Ø5x20
Power	50 W
Power Supply	AC100-230 V, 50/60 Hz

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com