

DIGITAL DISPLAY ULTRASONIC CLEANER ULC13-20



DIGITAL DISPLAY ULTRASONIC CLEANER

ULC13-20

Digital Display Ultrasonic Cleaner uses frequency of 40Khz for cleaning the lab equipments.
Also known as Digital ultrasonic cleaner, Ultrasonic cleaning bath, Ultrasonic cleaning tank.

ULC13-20 DIGITAL DISPLAY ULTRASONIC CLEANER

Digital display and control

Industrial high Q transducers, cleaning conversion efficiency is higher

No stud- welding technology, Cleaning effect is better

MCU SWEEP multi frequency ultrasonic generator output, frequency sweep drive ultrasonic cleaning effect more powerful

MHC heating system, maximum temperature is up to 80°C

All stainless steel material inner tank is made by punching SUS304 1.0mm

2500V high voltage test to ensure the product safety, strict production, aging production quality control



SPECIFICATIONS

Model	ULC13-20
Capacity	20 L
Working frequency	40 Khz
Ultrasonic Power	360 W
Heating power	400 W/220V 400 W/110V
Timing time	1- 99 mins
Temperature range	0- 80°C
Cover	Yes
Drain valve	Yes
Washing basket	Optional
Inner tank dimension	330x300x200 mm
Packing size	472x437x470 mm
Gross weight	12.5 Kg
Power Supply	220V+ 10% 50Hz/60Hz 110V+ 10% 50Hz/60Hz

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@mail.labstac.com | Website: labstac.com