

# CARBURETOR ULTRASONIC ULC16-68



# CARBURETOR ULTRASONIC ULC16-68

Carburetor Ultrasonic Cleaner uses ultrasonic waves to clean the smallest part of the lab tool with strong degreasing chemical.

Also known as Digital ultrasonic cleaner, Ultrasonic cleaning bath, Ultrasonic cleaning tank.

## ULC16-68 CARBURETOR ULTRASONIC

LCD display and control, simple operation

One key degassing can quickly remove air in water and ultrasonic cleaning effect is better

Independently developed MCU SWEEP ultrasonic generator drive, uniform and strong ultrasonic effect

Independently developed industrial high Q value transducer with high ultrasonic conversion efficiency and long service life

Power adjustment function can meet different cleaning requirements

Imported high strength glue Seedless nail bonding process, high ultrasonic conversion efficiency

Digital timing cleaning time 10S-100 min and digital heating control temperature 20-80C arbitrary settings

The inner groove adopts imported SUS304, 1.0mm stainless steel stamping, ultrasonic exchanger effect is better effect is better and longer and service life

The washing basket is made up of high quality 304 stainless steel mesh welding surface electrolyte polishing treatment

The shell is made up of high quality stainless steel with better anti corrosion effect



## SPECIFICATIONS

Model	ULC16-68
Capacity	6.8 L
Working frequency	39+ 1.5Khz
Ultrasonic Power	180 W
Heating power	200 W
Temperature range	20- 80°C
Power regulation	0-100 %
Drain valve	Yes
Washing basket	Optional
Cover	Yes
Degas	Yes
Inner tank dimension	300x150x150 mm
Packing size	402x252x355 mm
Gross weight	6.2 Kg
Power Supply	220V+ 10% 50Hz/60Hz 110V+ 10% 50Hz/60Hz

***LABSTAC***

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA  
Email: [contact@mail.labstac.com](mailto:contact@mail.labstac.com) | Website: [labstac.com](http://labstac.com)