

# DOUBLE ADJUSTABLE FREQUENCIES ULTRASONIC CLEANER ULC18-10A



# DOUBLE ADJUSTABLE FREQUENCIES ULTRASONIC CLEANER ULC18-10A

Double adjustable frequencies ultrasonic cleaner uses frequency of 45 KHz /80 KHz with strong penetrating power and an appropriate cleaning solvent to clean items.

Also known as Digital ultrasonic cleaner, Ultrasonic cleaning bath, Ultrasonic cleaning tank.

## ULC18-10A DOUBLE ADJUSTABLE FREQUENCIES ULTRASONIC CLEANER

Over- Voltage and over current protection

Standard basket and lid

Low level water protection

Fully microprocessor controller and programmable

Time and temperature real time display

Standard power supply AC220+10%, 50/60Hz: 110V+10%, 60Hz



### SPECIFICATIONS

Model	ULC18-10A
Capacity	10 L
Adjustable ultrasonic frequency	45 KHz /80 KHz
Time range/ Heating temp	1-480 mins / RT-80°C
Ultrasonic power	300 W
Heating power	400 W
Tank size	300x240x150 mm
Packing Size	446x346x483 mm
Gross Weight	12.5 Kg

# LABSTAC

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: [contact@labstac.com](mailto:contact@labstac.com) | Website: [labstac.com](http://labstac.com)