

DOUBLE ADJUSTABLE FREQUENCIES ULTRASONIC CLEANER ULC18-13A



DOUBLE ADJUSTABLE FREQUENCIES ULTRASONIC CLEANER ULC18-13A

Double adjustable frequencies ultrasonic cleaner uses frequency of 45 Khz /80 Khz with strong penetrating power and an appropriate cleaning solvent to clean items.

Also known as Digital ultrasonic cleaner, Ultrasonic cleaning bath, Ultrasonic cleaning tank.

ULC18-13A DOUBLE ADJUSTABLE FREQUENCIES ULTRASONIC CLEANER

Over- Voltage and over current protection

Standard basket and lid

Low level water protection

Fully microprocessor controller and programmable

Time and temperature real time display

Standard power supply AC220+10%, 50/60Hz: 110V+10%, 60Hz



SPECIFICATIONS

Model	ULC18-13A
Capacity	13 L
Adjustable ultrasonic frequency	45 Khz /80 Khz
Time range/ Heating temp	1-480 mins /0- 80°C
Ultrasonic power	300 W
Heating power	400 W
Tank size	300x240x180 mm
Packing Size	840x670x730 mm
Gross Weight	73 Kg

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com