

# -10°C TO -60°C ULTRA LOW TEMPERATURE FREEZER ULT91-485



# -10°C TO -60°C ULTRA LOW TEMPERATURE FREEZER ULT91-485

Innovative design and highly efficient for the user to use them for storing laboratory materials such as vaccines, biological samples, enzymes and protein samples. Excellent temperature uniformity, reliable environment monitoring and rust free construction supports this product to become an ideal choice.

Used in Routine Cold Storage, Laboratories, Biologicals, Pharmaceuticals, Clinical, Research.

Also known as Laboratory ULT freezer, ULT Freezer, Ultra-low Freezer.

## ULT91-485 -10°C TO -60°C ULTRA LOW TEMPERATURE FREEZER

LED digital display and increment at 0.1°C

Permanently lubricated cooling fan for safety and longevity

Independent inner door to avoid more cooling leaking out, and provide more stable inside temperature performance

High density CFC-Free urethane foam insulation

Chemically stable, CFC -free, commercially available and environmentally safe refrigerant

Corrosion proof cabinet interior design

Optimized refrigeration system designed to maximize cooling effect and temperature uniformity

Power failure protect: the device would be attack by the high current when all devices restart simultaneously, the start-delay function would protect device from the damage

Wide voltage tolerance design with applicable voltage range of 187-242V/AC

Audible buzzing and visual flashing light



### SPECIFICATIONS

Model	ULT91-485
Capacity	485 L
Temperature Range	-25°C to -60°C
Ambient Temperature	10°C ~ +32°C
Defrosting	Manual
Cooling Type	Direct Cooling
Insulation Material	PURF
Refrigerant	CFC-Free
Internal Dimension	1455x525x665 mm
Overall Dimension	1655x755x915 mm
Package Size	1750x900x1040 mm
Interior	Stainless steel
Exterior	Color sprayed steel
Controller	Microprocessor, Digital display
Sensor	PTC
Compressor Brand/QTY	CUBIGEL/1
Noise Level	55 db
Alarm	High/low temperature, Sensor malfunction, Thermostat failure

Standard Accessories	Caster, Test hole 1/25 mm
Optional Accessories	Temperature recorder
Weight (Net/Gross)	124 / 138.5 kg
Rated Power	450 W
Power Consumption ( Kwh/24hrs )	8.05
Power Supply	220V, 50Hz

**LABSTAC**

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: [contact@labstac.com](mailto:contact@labstac.com) | Website: [labstac.com](http://labstac.com)