

LIQUID SUCTION VACUUM PUMP VAP11-26



LIQUID SUCTION VACUUM PUMP VAP11-26

The liquid suction filtration vacuum pump series is mainly used for separation of culture fluid and culture tissue after biochemical culture, extraction of cell culture waste liquid, and suction of various waste liquids in the laboratory. Different flow specifications are available to meet more experimental needs, and it is the best experimental assistant indispensable for the laboratory aseptic workstation.

Used in Separation of culture fluid, Culture tissue, Biochemical culture, Extraction of cell culture waste liquid, Laboratory, Research, Medical..

Also known as Laboratory Liquid Suction Vacuum Pump.

VAP11-26 LIQUID SUCTION VACUUM PUMP

Pumping filter brackets are equipped on both sides of the instrument, easy to store and select the suction filter accessories

Standard equipped with multi-function suction filter handle and 5 kinds of suction head accessories to meet more requirements of suction experiments

Sealed waste liquid bottle cap design, quick-insertion sealing joint, convenient to get out of the fuselage bottle and clean up waste liquid

Normally open control mode and foot switch control mode, to meet more experimental requirements

Waste liquid bottle, suction filter fittings and dish filter can all be used for autoclave sterilization

There is a liquid level protection switch in the waste liquid bottle to prevent the waste liquid from overflowing and being sucked into the pump chamber to ensure no troubles in suction filtration

There is a PTFE dish shape filter between the bottle and the pump to protect the environment from harmful gas pollution

The self-locking quick connector can be quickly and easily separated from the pipeline, which is convenient for safely cleaning the waste bottle

Built-in high quality oil-free vacuum pump, no maintenance, low noise and long life



SPECIFICATIONS

Model	VAP11-26
Max. Flow rate	26 L/min
Vacuum degree	-0.08 Mpa
Vacuum display mode	Vacuum gauge
Negative pressure adjustment range	0~-0.08 Mpa
Waste liquid bottle capacity	2500 mL
Foot switch	Yes
Voltage	AC220 V/AC110 V 50/60 Hz
Power	60 W
Fuse	250 V 1 A, ϕ 5X20
Dimension (WxDxH)	248x475x350 mm
Net weight	7.8 kgs

ACCESSORIES

Accessory Code	Name	Material	Quantity
5800505005	Hand-held operator	POM	1
5800505006	Eight-channel retractable tip plastic extraction head	POM	1
5800505007	Eight channel stainless steel extraction head	POM+SUS304	1
5800505008	Single channel plastic extraction head	POM	1
5800505009	Single channel retractable tip plastic head	POM	1
5800505010	Single channel stainless steel extraction head	POM+SUS304	1
5800505011	Foot switch	AI	1

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com