

DRY BATH



DRY BATH

Laboratory Dry Bath

Used in Clinical, General Chemistry, Preservation, Reactions of sample, DNA amplification, Initial Denaturation of electrophoresis.

Also known as Laboratory Dry Bath.

BAC23-100 MINI DRY BATH



SPECIFICATIONS

Model	BAC23-100
Capacity	4 L
Function	Heating function
Temperature Range	+5°C~100°C
Temperature Uniformity	≤±0.3°C
Cleaning Tank (LxWxH)	300x150x100 mm
Outer Dimension (WxDxH)	420x230x270 mm
Weight	0.5 kg
Maximum Input Power	450
Maximum Output Power	180
Heating Power	250
Power Adjustable (%)	30-100
Drain	NO
Level Control System	NO
Power Supply	AC 100-240 V, 50 / 60 Hz

BAC21-060 AIR BATH



SPECIFICATIONS

Model	BAC21-060
Temp. Control Range	R.T.+5°C~60°C
Temp. Setting Range	5°C~60°C
Temp. Stability@37°C	±0.2°C
Temp. Uniformity	±0.5°C
Temp. Display Accuracy	0.1°C
Time Range	1min~99h59min
Fan Speed Range	1200~3200rpm
Incubation Space Size	L.245 x W.215 x H.85mm
Voltage	AC 220V/AC 110V, 50/60Hz
Power	300W
Fuse	250 V, 2A/4A, φ5x20
Dimension	W.275 x D.395 x H.150mm
Net Weight	8.1 kgs

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com