

# DRY BATH CHILLER



# DRY BATH CHILLER

Laboratory Dry Bath Chiller

Used in Clinical, General Chemistry, Preservation, Reactions of sample, DNA amplification, Initial Denaturation of electrophoresis.

Also known as Laboratory Dry Bath Chiller.

## BAC71 DRY BATH CHILLER



### SPECIFICATIONS

| Model                         | BAC71-00         | BAC71-16          |
|-------------------------------|------------------|-------------------|
| Capacity                      | 4 L              | 6 L               |
| Function                      | Basic model      | Heating function  |
| Temperature Range             | Maintains at 0°C | Maintains at 16°C |
| Temperature Uniformity        | ±0.5°C           |                   |
| Cleaning Tank (LxWxH)         | 300x150x100 mm   | 300x150x150 mm    |
| Outer Dimension (WxDxH)       | 420x230x270 mm   | 420x230x320 mm    |
| Weight                        | 1.4 kg           |                   |
| Temperature Precision         | ±0.5°C           |                   |
| Operation Ambient Temperature | 8-30°C           |                   |
| Maximum Input Power           | 220              | 450               |
| Maximum Output Power          | 180              |                   |
| Heating Power                 | NO               | 250               |
| Power Adjustable (%)          | NO               | 30-100            |
| Drain                         | NO               |                   |
| Level Control System          | NO               |                   |
| Power Supply                  | 12 V DC, 7A      |                   |



BAC71-00



BAC71-16

## BAC71-00A DRY BATH CHILLER

- PID controller offers precise temperature control and uniformity
- Corrosion resistant inner and outer chamber made of stainless steel
- Dual LED screen displays temperature and time
- Protection against compressor overload, high/low voltage and current
- Convenient and reliable operation
- Equipped with caster for easy installation



### SPECIFICATIONS

|                               |                  |
|-------------------------------|------------------|
| Model                         | BAC71-00A        |
| Capacity                      | 6 L              |
| Function                      | Power adjustable |
| Temperature Range             | Maintains at 0°C |
| Temperature Uniformity        | ±0.5°C           |
| Cleaning Tank (LxWxH)         | 300x150x150 mm   |
| Outer Dimension (WxDxH)       | 185x185x90 mm    |
| Weight                        | 1.4 kg           |
| Temperature Precision         | ±0.5°C           |
| Operation Ambient Temperature | 8-30°C           |
| Maximum Input Power           | 220              |
| Maximum Output Power          | 180              |
| Heating Power                 | NO               |
| Power Adjustable (%)          | 30-100           |
| Drain                         | NO               |
| Level Control System          | NO               |
| Power Supply                  | 12 V DC, 7A      |

***LABSTAC***

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA  
Email: [contact@labstac.com](mailto:contact@labstac.com) | Website: [labstac.com](http://labstac.com)