

ROCKING SHAKER



ROCKING SHAKER

Rocking Shaker are designed to deliver salient performance, accuracy, and reproducible results for all your application needs. Lightweight and portable for easy transfer, outstanding uniform motion, high quality stain resistant platforms with non-slip rubber mats and low noise are the efficient and reliable features that makes it unique.

Used in Laboratory, Research, Mixing, Incubation.

Also known as Laboratory Rocking Shaker.

SHA61-20 3D GYRATORY ROCKER

Gentle but thorough mixing

Suits for blood collection tubes and centrifuge tubes

Tilt angle and speed have been optimally set

Safe for use in cold rooms and incubators



SPECIFICATIONS

Model	SHA61-20
Speed Range	20 rpm (fixed)
Shaking Orbit	3D / 20 (fixed)
Max. Load	0.8 kgs
Voltage	AC 220V/AC 110V, 50/60 Hz
Power	45 W
Dimension	W.240 x D.170 x H.150 mm
Net Weight	1.6 kgs

SHA62-25 DECOLORISING SHAKER

Rocking angle adjustable

Speed adjustable

Time setting



SPECIFICATIONS

Model	SHA62-25
Speed Range	0-25 rpm
Angle Range	±25°C
Inner Dimension	250x200 mm
Overall Dimension	420x200x200 mm
Weight	2.5 kg
Power Supply	AC 80-230 V 50/60 Hz

SHA63 ROCKING SHAKER

Platform made of stainless steel and natural rubber, which is alkali-resistance, non-defomation, easy-clean and spill-prevention

Speed real-time display and diminishing time display

The bearing is articulaed rotating, secure and no wear, suitable for long time use

Compact designed, take very little space

Brushless DC motor, free maintenance



SPECIFICATIONS

Model	SHA63-80	SHA63-80C
Speed Range	5-80 rpm	
Swing Cycloid	25 mm(Up and Down) / 10°	
Timing Range	1 min~99 h 59 min	
Maximum Load Capacity	5 kg(single-deck platform)	5 kg(double-deck platform)
Platform Dimension	L.280 x W.228 mm	
Overall Dimension	284x264x134 mm	
Weight	5.2 kg	6.0 kg
Fuse	250 V,1 A, Φ5x20	
Power	50 W	
Power Supply	AC100-230 V, 50/60 Hz	

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com