

AIR SHOWER



AIR SHOWER

BSC71 AIR SHOWER

Photoelectric sensor, automatic blowing

Adopt with circulation wind to ensure the cleanness of shower area under non-shower status

Double door by electric interlock

LED display with adjustable blowing time (0-99s)

HEPA filter, Class 100 cleanness

SPECIFICATIONS

Model	BSC71-0550	BSC71-1100	BSC71-2200
External Size (WxDxH)	1300x1000x2050 mm	1500x1000x2050 mm	1500x2000x2050 mm
Internal Size (WxDxH)	800x900x1930 mm		800x1900x1930 mm
HEPA filter	99.995 % efficiency at 0.3 μ m		
Spraying Wind Speed	25 m/s		
Air Shower time	0-99 s (adjustable)		
No. of SS Nozzels	6	12	24
Fluorescent Lamp	12Wx1		
Consumption	550 W	1100 W	2200 W
Cabinet Material (Optional)	1.Full cold-rolled steel with powder coating 2.Internal stainless steel, external with cold-rolled steel 3.Full stainless steel		
Door Material (Optional)	1.Cold-rolled steel with powder coating 2.Stainless steel		
Chassis	Stainless Steel		
Power Supply	AC220 V \pm 10%,50/60 Hz ; 110 V \pm 10%, 60 Hz		
Gross Weight	300 kg	400 kg	700 kg
Package Size (WxDxH)	1400x1200x2200 mm	1600x1200x2200 mm	1600x2200x2200 mm



BSC71-1100



BSC71-2200

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com