

VERTICAL LAMINAR AIRFLOW



VERTICAL LAMINAR AIRFLOW

Engineered to create a particle-free working environment and provide product protection. It is suited for use with non-hazardous contaminants and creates a clean work environment over a wide range of applications.

Used in Electronic sectors, Industrial sectors, Medical, Pharmaceutical, Healthcare.

Also known as Tissue Culture Hood, Laminar Air Flow Cabinet, Laboratory Laminar Flow, Laboratory Laminar Air Flow, Laminar Flow Cabinet, Minimal-Turbulence Air Flow, Laminar Flow Cabinet, Laminar Flow Hood, Laminar Flow.

LAF31 VERTICAL LAMINAR AIR FLOW

Microprocessor controller

Pre-filter: Polyester fiber, washable

UV Lamp: Emission of 253.7 nanometers

Waterproof socket: Two, total load $\leq 500W$

Display Airflow velocity, UV timer, UV work time, system work time, real time



SPECIFICATIONS

Model	LAF31-1200	LAF31-1700
Type	Vertical Laminar Flow	
Airflow Velocity	Average of 0.3~0.5m/s	
HEPA Filter	99.999% efficiency at 0.3 μ m	
Pre-filter	Polyester fiber, washable	
Work Surface Height	750mm	
Main Body Material	Cold-rolled steel with anti-bacteria powder coating	
Work Table Material	304 stainless steel	
Side and Front Window Material	5mm toughened glass, anti-UV	
UV Lamp	30 Wx1 Emission of 253.7 nanometers	40 Wx1 Emission of 253.7 nanometers
LED Lamp	12W x1	16W x1
Display	LCD display	
Front Window	Motorized	
Max Opening	430 mm	
Caster	Universal caster with leveling feet	
Waterproof Socket	Two, total load $\leq 500W$	
Standard Accessory	LED lamp, UV lamp x2, Base stand, Gas Tap, Waterproof socket x2	
Optional Accessory	Electric height adjustable base stand	
Internal Size	1200Wx645Dx610 mm	1700Wx645Dx610 mm
External Size	1300Wx750Dx2040H mm	1800Wx750Dx2040H mm
Packaging Size	1460x1070x1650mm	1960x970x1600mm
Gross Weight	228kg	306kg
Noise	<65dB	

Consumption	400 W	450 W
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz	AC220V±10%, 50/60Hz; 110V±10%, 60Hz

LAF32-0630 VERTICAL LAMINAR AIR FLOW

Microprocessor controller

Pre-filter: Polyester fiber, washable

UV Lamp: Emission of 253.7 nanometers



SPECIFICATIONS

Model	LAF32-0630
Type	Vertical Laminar Flow
Air Flow Velocity	Average of 0.3~0.5m/s, air speed adjustable.
HEPA Filter	99.995% efficiency at 0.3µm
Pre-filter	Polyester fiber, washable
Work Surface Height	/
Max Opening	/
Front Window	/
UV Lamp	15Wx1 Emission of 253.7 nanometers
illuminating Lamp	Fluorescent lamp 8W*1
Display	LED Display
Main Body Material	Cold-rolled steel with anti-bacteria powder coating
Work Table Material	304 stainless steel
Caster	/
Standard Accessory	Fluorescent lamp; UV lamp x2; Water & gas tap.
Optional Accessory	/
Noise	<65dB
Internal Size	630Wx375Dx615H mm
External Size	680Wx410Dx1160 mm
Package Size	840Wx560Dx1380H mm
Gross Weight	50kg
Consumption	160W
Power Supply	AC220V±10%, 50/60 Hz; 110V±10%, 60Hz

LAF33-0800 VERTICAL LAMINAR AIR FLOW

Microprocessor controller

Pre-filter: Polyester fiber, washable

UV Lamp: Emission of 253.7 nanometers



SPECIFICATIONS

Model	LAF33-0800
Type	Vertical Laminar Flow
Air Flow Velocity	Average of 0.3~0.5m/s, air speed adjustable.
HEPA Filter	99.995% efficiency at 0.3 μ m
Pre-filter	Polyester fiber, washable
Work Surface Height	660mm
Max Opening	490mm
Front Window	Manual, 5mm toughened glass, anti-UV
UV Lamp	20Wx1 Emission of 253.7 nanometers
illuminating Lamp	LED lamp 8W*1
Display	LED Display
Main Body Material	Cold-rolled steel with anti-bacteria powder coating
Work Table Material	/
Caster	Universal wheel with leveling feet
Standard Accessory	LED lamp; UV lamp x2; Base stand;
Optional Accessory	Electric height adjustable base stand
Noise	<65dB
Internal Size	800x530Dx540H mm
External Size	802Wx650Dx1550 mm
Package Size	960Wx800Dx1800H mm
Gross Weight	116kg
Consumption	350W
Power Supply	AC220V \pm 10%, 50/60 Hz; 110V \pm 10%, 60Hz

LAF34 VERTICAL LAMINAR AIR FLOW

Microprocessor controller

Pre-filter: Polyester fiber, washable

UV Lamp: Emission of 253.7 nanometers



SPECIFICATIONS

Model	LAF34-0940	LAF34-1340
Type	Vertical Laminar Flow	
Air Flow Velocity	Average of 0.3~0.45m/s, air speed adjustable.	
HEPA Filter	99.995% efficiency at 0.3μm	
Pre-filter	Polyester fiber, washable	
Work Surface Height	750mm	
Max Opening	400mm	
Front Window	Manual, 5mm toughened glass, anti-UV	
UV Lamp	20Wx1 Emission of 253.7 nanometers	40Wx1 Emission of 253.7 nanometers
illuminating Lamp	LED lamp 12W*1	LED lamp 16W*1
Display	LCD Display	
Main Body Material	Cold-rolled steel with anti-bacteria powder coating	
Work Table Material	304 stainless steel	
Caster	Universal wheel with leveling feet	
Standard Accessory	LED lamp; UV lamp x2; Base stand.	
Optional Accessory	Electric height adjustable base stand	
Noise	<65dB	
Internal Size	935Wx530Dx650H mm	1335Wx530Dx650H mm
External Size	1060Wx620Dx1850 mm	1460Wx620Dx1850 mm
Package Size	1240Wx900Dx1350H mm	1640Wx900Dx1350H mm
Gross Weight	185kg	231kg
Consumption	150W	250W
Power Supply	AC220V±10%, 50/60 Hz; 110V±10%, 60Hz	



LAF34-0940



LAF34-1340

LAF35 VERTICAL LAMINAR AIR FLOW

Microprocessor controller

Double side work bench, operators can sit face to face

Pre-filter: Polyester fiber, washable

UV lamp: Emission of 253.7 nanometers



SPECIFICATIONS

Model	LAF35-0940	LAF35-1340
Type	Vertical Laminar Flow	
Air Flow Velocity	Average of 0.3~0.5m/s	
HEPA Filter	99.995% efficiency at 0.3μm	
Pre-filter	Polyester fiber, washable	
Work Surface Height	750mm	
Max Opening	310mm	
Front Window	Manual, 5mm toughened glass, anti-UV	
UV Lamp	20W*1 Emission of 253.7 nanometers	30W*1 Emission of 253.7 nanometers
LED Lamp	12W*1	16W*1
Display	LCD display	
Main Body Material	Cold-rolled steel with anti-bacteria powder coating	
Work Table Material	304 stainless steel	
Caster	Universal caster with leveling feet	
Standard Accessory	LED lamp, UV lamp x2, Base stand.	
Optional Accessory	Electric height adjustable base stand	
Noise	<65dB	
Internal Size	940Wx560Dx545H mm	1340Wx560Dx545Hmm
External Size	1040Wx660Dx1770 mm	1440Wx660Dx1770 mm
Package Size	1190Wx890Dx1340H mm	1590Wx890Dx1340H mm
Gross Weight	150kg	186kg
Consumption	350W	600W
Power Supply	AC220V±10%, 50/60 Hz; 110V±10%, 60 Hz	



LAF35-0940



LAF35-1340

LAF36 VERTICAL LAMINAR AIR FLOW

ETL certified, Satisfy North American market.

With memory function in case of power-failure.

Audio and visual alarm(Abnormal airflow velocity).

Interlock function: UV Lamp and blower LED Lamp.



SPECIFICATIONS

Model	LAF36-10L	LAF36-14L	LAF36-14LA
Type	The ETL certified vertical laminar flow cabinet		The ETL certified vertical laminar flow
Airflow Velocity	Average of 80~99 fpm		
HEPA Filter	One,99.995% efficiency at 0.3μm		
Pre-Filter	Polyester fiber		
Work Surface Height	750~1010mm		
Max Opening	480mm		
Working area Material	304 stainless steel		
Main Body Material	1.2mm Cold-rolled steel with anti-bacteria powder coating.		
Front Window Material	Motorized, 5mm toughened glass, anti-UV		
Waterproof Sockets	One socket (Double type), America standard, Max.Power: 500W		
UV Lamp	18W x1	30W x1	
LED Lamp	10W x1	14W x1	
Display	LCD Display		
Illumination	≥300lx		
Noise	≤68dB(A)		
Standard Accessory	Manually height adjustable base stand; LED lamp; UV lamp; Wind speed sensor; Waterproof socket.		
Internal Size	700Wx575Dx625H mm	1000Wx575Dx625H mm	1200Wx575Dx625H mm
External Size	800x700x(2090~2340)mm	1100x700x(2090~2340)mm	1300x700x(2090~2340)mm
Package Size	940Wx970Dx1560H mm	1240Wx970Dx1560H mm	1440Wx970Dx1560H mm
Gross Weight	190kg	230kg	265kg
Consumption	750W	950W	
Power Supply	110V±10%V, 60HZ		

Model	LAF36-18L	LAF36-22L
Type	The ETL certified vertical laminar flow	
Airflow Velocity	Average of 80~99 fpm	
HEPA Filter	One,99.995% efficiency at 0.3μm	
Pre-Filter	Polyester fiber	
Work Surface Height	750~1010mm	

Max Opening	480mm	
Working area Material	304 stainless steel	
Main Body Material	1.2mm Cold-rolled steel with anti-bacteria powder coating.	
Front Window Material	Motorized, 5mm toughened glass, anti-UV	
Waterproof Sockets	One socket (Double type), America standard, Max.Power: 500W	
UV Lamp	40W x1	
LED Lamp	18W x1	22W x1
Display	LCD Display	
Illumination	≥300lx	
Noise	≤68dB(A)	
Standard Accessory	Manually height adjustable base stand; LED lamp; UV lamp; Wind speed sensor; Waterproof socket.	
Internal Size	1400Wx575Dx625H mm	1700Wx575Dx625H mm
External Size	1500x700x(2090~2340)mm	1800x700x(2090~2340)mm
Package Size	1640Wx970Dx1560H mm	1940Wx970Dx1560H mm
Gross Weight	280kg	320kg
Consumption	950W	1150W
Power Supply	110V±10%V, 60HZ	



LAF36-10L



LAF36-14L



LAF36-14LA



LAF36-18L



LAF36-22L

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com