

PLATELET INCUBATOR



PLATELET INCUBATOR

Used in Platelet preservation, Food processing industries, Scientific, Research, Medical, Health, Laboratory, Pharmaceuticals, Microbial culturing.

Also known as Laboratory Platelet Incubator.

INCC1 PLATELET INCUBATOR

Microcomputer temperature controller

LCD Display

'Set temperature' and 'Actual temperature' display on double screen, clear and straight forward.

Air forced convection design, ensures the temperature uniform in the chamber.

Over temperature / Low temperature alarm, abnormal shutdown power outage alarm.

Sets in exchange stomatal, to ensure that the air is fresh in the cabinet.

UV Lamp in the cabinet.

Automatic defrost function.

Big observation window, working condition will be clear at a glance.

Stainless steel inner chamber material, easy to clean.

Heat preservation material, uses polyurethane foam.

Closed type compressor.

Less noise.



SPECIFICATIONS

Model	INCC1-030	INCC1-060	INCC1-120
Capacity	10 floors (20-30bags)	10/15/20 floors (40-60bags)	double doors, 20 floors for each sides, total 40 floors (80-120bags)
Temperature Range	15-35°C		
Temperature Accuracy	±0.1		
Timer Range	0-999		
Variation (%)	±0.5		
Internal Dimension	390Wx390Dx530H mm	590Wx390Dx820H mm	1090Wx390Dx950H mm
Exterior Dimension	670Wx600Dx1050H mm	670Wx600Dx1500H mm	1170Wx600Dx1750H mm
Tray Size (WxDxH)	480x300x390 mm	480x300x680 mm	980x300x810 mm
Weight	110 Kg	180 Kg	320 Kg
Power	0.5 KW	0.8 KW	1.35 KW



INCC1-030



INCC1-060



INCC1-120

INCC1 PLATELET INCUBATOR



SPECIFICATIONS

Model	INCC1-05L	INCC1-10L
Capacity	5 L/cu.ft	10 L/cu.ft
Cooling Method	Forced air cooling	
Defrost	No frost	
Refrigerant	R134a	
Temperature range	20~24°C	
Ambient temperature	10~32°C	
Compressor brand/QTY	EMBRACO/1	
Temperature controller	Microprocessor PID	
Sensor	NTC	
Display	Digital display	
Inside material	SUS	
Outside material	Colored Spray Steel	
Insulation Materials	PU	
Bloodbags(450ml)/Drawer	10 /5 layers	20 /10 layers
NT./GT.	65/87 Kg	85/108.5
Alarm System	High/low temperature, Power failure, Sensor malfunction, Door ajar, Power failure backup system(alarm)-72h	
Accessories	Caster, Outer door / Type - 1Foamed glass door,Test hole - Optional, Light - UV Light, Temperature recorder - Optional	
Shelf/drawer QTY	Drawer	
Internal Dimension	427Wx360Dx467H mm	432Wx462Dx728H mm
Exterior size	520Wx640Dx1030H mm	520Wx640Dx1290H mm
Package size(WxDxH)	590x695x1210 mm	575x690x1450 mm
CBM	0.5	0.58
20GP/40GP/40HQ	24/48/96	32/68/68
Noise	49 db	50 db
Power consumption (kWh/24h)	2.69 (kWh/24h)	4.4 (kWh/24h)
Voltage/frequency	220/50Hz	
Power	197 W	280 W
Current	0.9 A	1.27 A



INCC1-05L



INCC1-10L

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@labstac.com | Website: labstac.com