

NATURAL CONVECTION OVEN



NATURAL CONVECTION OVEN

OVE060 NATURAL CONVECTION OVEN

With reservation and Timer functions, there is no need to wait, which effectively improves the efficiency of the experiment

Available in Chinese and English menus to meet different language needs, with °C / °F conversion

The height of the shelf is adjustable to meet different cultivation needs

Professional stacking foot design, the machine can be stacked, saving lab space and improving the use efficiency

Protection on instruments: Comply international standard secondary temp limiting alarm system, when the heating is out of control or exceeds the maximum limit temperature

the heating is automatically cut off with sound and light alarm, ensure operating is safe without any accident

Protection on key components: Key components are equipped with over-current, over-temperature, overload and other safety protection to prevent accident

Protection on samples: When the temperature inside the box is higher or lower than the set temperature, the alarm will start to cut off the heater, with sound and light alarm to remind the operator to protect the sample from normal test without accident

Protection on operator: The cabinet and door are specially insulated to make the surface temperature of the cabinet low, ensuring the operator's safety and no accidents

Breakdown message provided: When the instrument breakdown, the message will shown on the screen to help operator clearly check

The touch screen type standard with a USB interface, which can record the change status of the temperature parameters

The LCD screen is option for USB interface

It can be equipped with RS232 data interface, which can realize remote control of the machine through software

RS-232 and USB can be selected one of them



SPECIFICATIONS

Model	OVE060-034	OVE060-054	OVE060-124	OVE060-222
Capacity	34 L	54 L	124 L	222 L
Temperature Range	RT+10°C-200°C (MAX 300°C)			
Display Resolution	0.1°C			
Uniformity at 100°C	±2.5°C			
Heated to 100°C	25 mins			
Standard Max number of shelves	2 (5)	2 (6)	2 (10)	2 (16)
Max load per shelf	20 Kg			
NW	43 Kg	45 Kg	74 Kg	103 Kg
Timer Range	1 - 5999 mins			
Internal Dimension	320Wx300Dx360H mm	400Wx330Dx415H mm	520Wx450Dx530H mm	650Wx500Dx685H mm
Exterior Dimension	610Wx520Dx580H mm	690Wx468Dx640H mm	810Wx590Dx755H mm	940Wx658Dx910H mm
Electrical Requirement	AC 220 V, 50 Hz			
Power Consumption	850 W	1050 W	1950 W	2250 W



OVE060-034



OVE060-054



OVE060-124



OVE060-222

OVE061 NATURAL CONVECTION OVEN

With reservation and Timer functions, there is no need to wait, which effectively improves the efficiency of the experiment

Available in Chinese and English menus to meet different language needs, with °C / °F conversion

The height of the shelf is adjustable to meet different cultivation needs

Professional stacking foot design, the machine can be stacked, saving lab space and improving the use efficiency

Protection on instruments: Comply international standard secondary temp limiting alarm system, when the heating is out of control or exceeds the maximum limit temperature

the heating is automatically cut off with sound and light alarm, ensure operating is safe without any accident

Protection on key components: Key components are equipped with over-current, over-temperature, overload and other safety protection to prevent accident

Protection on samples: When the temperature inside the box is higher or lower than the set temperature, the alarm will start to cut off the heater, with sound and light alarm to remind the operator to protect the sample from normal test without accident

Protection on operator: The cabinet and door are specially insulated to make the surface temperature of the cabinet low, ensuring the operator's safety and no accidents

Breakdown message provided: When the instrument breakdown, the message will shown on the screen to help operator clearly check

The touch screen type standard with a USB interface, which can record the change status of the temperature parameters

The LCD screen is option for USB interface

It can be equipped with RS232 data interface, which can realize remote control of the machine through software

RS-232 and USB can be selected one of them



SPECIFICATIONS

Model	OVE061-034	OVE061-054	OVE061-124	OVE061-222
Capacity	34 L	54 L	124 L	222 L
Temperature Range	RT+10°C-200°C (MAX 300°C)			
Display Resolution	0.1°C			
Uniformity at 100°C	±2.5°C			
Heated to 100°C	25 mins			
Standard Max number of shelves	2 (5)	2 (6)	2 (10)	2 (16)
Max load per shelf	20 Kg			
NW	43 Kg	45 Kg	74 Kg	103 Kg

Timer Range	1 - 5999 mins			
Internal Dimension	320Wx300Dx360H mm	400Wx330Dx415H mm	520Wx450Dx530H mm	650Wx500Dx685H mm
Exterior Dimension	610Wx520Dx580H mm	690Wx468Dx640H mm	810Wx590Dx755H mm	940Wx658Dx910H mm
Electrical Requirement	AC 220 V, 50 Hz			
Power Consumption	850 W	1050 W	1950W	2250W



OVE061-034



OVE061-054



OVE061-124



OVE061-222

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: contact@labstac.com | Website: labstac.com