

HYDROGEN GENERATOR



HYDROGEN GENERATOR

Engineered to provide a safe, ultrahigh-purity alternative to high-pressure gas cylinders in the laboratory for carrier and fuel gas applications, most often in gas chromatography. It is compact, reliable, practical and cost-effective alternative to pressurized cylinders. Due to hydrogen's flammability, the importance of safety features is paramount.

Used in Gas quality monitoring, General laboratory, Gas chromatography, TOC, Industries, Environmental, Petrochemical, Pharmaceutical, Cinical, Forensics..

Also known as Laboratory Hydrogen Generator.

GEN23-1000 AUTOMATIC HYDROGEN GENERATOR

Automatic control, constant pressure, constant flow

Membrane separation technique, deoxidation and dehydration device, high purity

Easy operation, eliminate the need for expensive gas cylinder

Safe and reliable



SPECIFICATIONS

Model	GEN23-1000
Environmental Temperature	0-45°C
Flow Rate	0-1000 ml / min
Output Pressure	0-0.4 Mpa
Pressure Stability	<0.001 Mpa
Dimension	460x370x360mm
Net Weight	20 kg
Consumption Power	400 W
Power Supply	220 V±10%, 50V

GEN21-0200 AUTOMATIC HYDROGEN GENERATOR

Automatic control, constant pressure, constant flow
 Membrane separation technique
 Compact, frees up valuable space
 Easy operation, eliminate the need for expensive gas cylinder
 Safe and reliable



SPECIFICATIONS

Model	GEN21-0200
Hydrogen purity	100.00%
Hydrogen Flow Rate	0-200 ml/min
Output Pressure	0-0.3 MPa
Pressure Stability	< 0.001MPa
Dimension	200x140x290 mm
Net Weight	6 kg
Consumption Power	100 W
Power Supply	220V±10%, 50Hz

GEN21 AUTOMATIC HYDROGEN GENERATOR

Automatic control, constant pressure, constant flow
 Membrane separation technique
 Deoxidation and dehydration device, high purity
 Compact, frees up valuable space
 Easy operation, eliminate the need for expensive gas cylinder
 Safe and reliable



SPECIFICATIONS

Model	GEN21-0300	GEN21-0500
Hydrogen purity	100.00%	
Flow Rate	0-300 ml / min	0-500 ml / min
Output Pressure	0-0.4 Mpa	0-0.6 Mpa
Pressure Stability	<0.001 Mpa	
Dimension	370x330x180 mm	

Net Weight	10 kg	
Consumption Power	150 W	250 W
Power Supply	220 V±10%, 50 Hz	



GEN21-0300



GEN21-0500

GEN22 AUTOMATIC HYDROGEN GENERATOR

SPE (Solid Polymer Electrolytes) technique, without lye
 Automatic control, pressure controller, water shortage detector
 Deoxidation and Dehydration device, high purity
 Easy operation and maintenance, long lifetime
 Compact design, Safe and reliable
 CE approved



SPECIFICATIONS

Model	GEN22-0300	GEN22-0500
Hydrogen purity	100.00%	
Flow Rate	0-300 ml / min	-
Output Pressure	0-0.4 Mpa	
Pressure Stability	<0.001 Mpa	<0.003 Mpa
Dimension	400x360x220 mm	460x360x350 mm
Net Weight	14 kg	20 kg
Consumption Power	150 W	
Power Supply	220 V±10%, 50 Hz	
Hydrogen Flow Rate	-	0-500 ml / min



GEN22-0300



GEN22-0500

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@labstac.com | Website: labstac.com