

# DELIVERY TABLE



# DELIVERY TABLE

The Delivery table is a flexible designed for suitable in conducting parturient delivery, gynecological surgery, operative abortion, diagnosis and examinations etc. by medical unit. It has an array of user-friendly features. The table has been designed keeping in mind the safety and comfort of the patient to support throughout the stages of delivery.

Used in Gyneacological surgery, Operative abortion, Gyneacological examination, Labor, delivery, postpartum recovery period, Parturient delivery, Diagnosis, Ultrasonic examination, Gynecological abdominal operation, Vulva operation. Also known as Gyneacological table, Gyneacological bed, Examination table, Examination bed, Delivery bed, Gynaecological Delivery Bed.

## HBD33-MO MANUAL OBSTERIC BED

The main bed and auxiliary bed are connected with each other, four foot wheels are equipped on auxiliary bed and brake device is spared

Foot step hydraulic elevating, Imported Y type sealing ring and is durable

The mattress adopts high density memory sponge and is once formed, easily cleaned and sterilized

Rotary brake device which is easy for moving operating table

Base seat and upright column covering are made of high quality 304 stainless steel



## SPECIFICATIONS

|                           |  |
|---------------------------|--|
| Model                     | HBD33-MO   |
| Length                    | 1950+50 mm   |
| Width                     | 600+50 mm  |
| Height Adjustment         | (750~950)+50 mm  |
| Working area length/width | 650x600 mm   |
| Backboard upward          | ≥50°   |
| Backboard downward        | ≥10°   |
| Seat board upwards        | ≥30°   |
| Seat board downwards      | ≥10°   |
| Standard accessory        | A pair of arm rods, a pair of leg support, a pair of arm rods, a pair foot pedal, a stainless steel sewage basin |

## HBD34-EG ELECTRIC GYNECOLOGICAL TABLE

Various actions are controlled by Imported brand motor

Hand-held controller and foot controller, mutually independent and is easily for operation

Leg support frame can fold up and down electric

Unique profile design which is beautiful and elegant

Whole stainless steel hidden auxiliary table with flexible extension and retraction

Equipped with hidden sewage basin

The table adopts high density memory sponge and is once foam molding, with no seam

Features with one-key reset function

Super mute foot wheel and equipped with brake device



### SPECIFICATIONS

|   |   |
|---|---|
| Model                                       | HBD34-EG  |
| Back board length                           | 900 mm  |
| Seat board length                           | 400 mm  |
| Table width                                 | 600 mm  |
| Trendelenburg/rev-trend                     | $\geq 10^\circ/\geq 12^\circ$   |
| Backboard Adjustment                        | $\geq 45^\circ$   |
| Height adjustment (from back top to ground) | 1500-1750 mm  |
| Standard Accessory                          | A pair of arm rods, a pair of leg support, a stainless steel sewage basin, auxiliary table (already installed), a foot controller |

## HBD35-EO ELECTRIC OBSTERIC BED

Imported LINAK motor various actions are controlled by remote controller

Super mute big foot wheel which is easily moved and equipped with center control breaking system.

Equipped with stainless steel sewage basin

The mattress adopts high density sponge and manufactured by high quality artificial leather without seam

With various complete accessories

Standard Accessories: A pair of leg support frame, a stainless steel sewage basin, a stand for transfusion, a remote control, a power wire



### SPECIFICATIONS

|                         |                              |
|-------------------------|------------------------------|
| Model                   | HBD35-EO                     |
| Length                  | 1950+50 mm                   |
| Width                   | 800+50 mm                    |
| Height Adjustment       | (550~800)+50 mm              |
| Trendelenburg/rev-trend | $\geq 5^\circ/\geq 12^\circ$ |
| Backboard upward        | $\geq 60^\circ$              |

|                     |   |
|---------------------|---|
| Foot board upward   | $\geq 40^\circ$   |
| Foot board downward | $\geq 90^\circ$   |
| Standard accessory  | A pair of leg support, a sewage basin, a power cord, a IV pole, a remote controller |
| Input power         | 150+10%   |
| Power Supply        | 220+22V, 50+1Hz   |

## HBD36-MM MANUAL MULTI-FUNCTION GYNEACOLOGICAL TABLE

Material: Steel Powder Coated S.S, Color: Blue



### SPECIFICATIONS

|                          |                       |
|--------------------------|-----------------------|
| Model                    | HBD36-MM              |
| Function                 | Multi                 |
| Back-rest lifting angle  | $\geq 20^\circ$       |
| Back section up adjusted | $\geq 60^\circ$       |
| Seat board upwards       | $\geq 8^\circ$        |
| Seat board downwards     | $\geq 10^\circ$       |
| Load Bearing             | 250 kg                |
| Height adjustment        | $\leq 650$ mm         |
| Tabletop Dimension       | 1240Lx600W mm         |
| Upright Dimension        | 500Lx600W mm          |
| Dimension                | 1750Lx600Wx650~900 mm |

## HBD38-2000 ELECTRIC GYNECOLOGICAL TABLE

Imported LINAK motor various actions are controlled by foot controller

The base seat and upright column covering are made of high quality 304 stainless steel which is anti corrosive and can be easily clean

External folding auxiliary table is for easy dismantling

Equipped with stainless steel sewage basin and other accessories

Foot treadle brake device which is easy for moving obstetric table



### SPECIFICATIONS

|                           |  |
|---------------------------|--|
| Model                     | HBD38-2000   |
| Table Length              | 2000+50 mm   |
| Table width               | 600+10 mm  |
| Height Adjustment         | (650-900)+50 mm  |
| Trendelenburg/rev-trend   | $\geq 10^\circ / \geq 12^\circ$  |
| Backboard upward          | $\geq 50^\circ$  |
| Leg board outward         | $\geq 90^\circ$  |
| Working area length/width | 600x600 mm   |
| Standard accessory        | A pair of arm support, a pair of leg support, a pair of foot pedal, a pair of foot arm rods, a stainless steel sewage basin, a foot controller |

## HBD38-1270 ELECTRIC GYNECOLOGICAL TABLE

Various actions are controlled by Imported LINAK motor

Hand-held remote control and pedal remote control, independent of each other, easy to operate it

With concealed stainless steel sewage waste basin

The mattress is wrapped with imported artificial leather. High density memory sponge is formed in one piece, with no seam

Equipped with brake device which is easy for moving the table

The base is made up of high strength ABS, which is corrosion resistant and easy to clean

Leg plate can be lifted electrically

Concealed stainless steel auxiliary table

With function of auto restoration



### SPECIFICATIONS

|                   |                  |
|-------------------|------------------|
| Model             | HBD38-1270       |
| Table Length      | 1270+50 mm       |
| Table width       | 550+30 mm        |
| Height Adjustment | (700-1000)+50 mm |

|                         |  |
|-------------------------|--|
| Trendelenburg/rev-trend | $\geq 5^\circ / \geq 12^\circ$   |
| Backboard downward      | $\geq 40^\circ$  |
| leg board reflex        | $\geq 30^\circ$  |
| Working area            | (350x480)+20 mm  |
| Standard accessory      | A pair of arc shaped handle, a pair of leg support, a stainless steel sewage basin, a power cord, a hand held remote controller, a foot controller |
| Main Voltage AC         | 220V+22V, 50Hz+1Hz   |

## HBD38-1300 ELECTRIC GYNECOLOGICAL TABLE

Adopt high density memory sponge and is once formed, with no seam  
 Hydraulic lifting by foot pedal, other actions are controlled by pneumatic  
 Imported Y shaped sealing ring and durable  
 Stainless steel concealed auxiliary table  
 The base is made up of high strength ABS  
 Equipped with foot brake device which is easy for moving the table



### SPECIFICATIONS

|                                 |   |
|---------------------------------|---|
| Model                           | HBD38-1300  |
| Table Length                    | 1300+50 mm  |
| Table width                     | 550+30 mm   |
| Height Adjustment               | (700 950)+50 mm   |
| Trendelenburg/rev-trend         | $\geq 3^\circ / \geq 10^\circ$  |
| Dimension of auxiliary platform | (350x450)+20 mm   |
| Backboard downward              | $\geq 70^\circ$   |
| Standard Accessory              | A pair of arm rods, a pair of leg support, a stainless steel sewage basin |

## HBD38-1450 ELECTRIC GYNECOLOGICAL TABLE

Whole stainless steel hidden auxiliary table with flexible extension and retraction  
 Equipped with hidden sewage basin  
 With foot control, can adjust the movements easily  
 Imported LINAK gear motor, without noise, have a long service life



## SPECIFICATIONS

|                         |   |
|-------------------------|---|
| Model                   | HBD38-1450  |
| Table Length            | 1450+50 mm  |
| Table width             | 520+30 mm   |
| Height Adjustment       | (400 900)+50 mm   |
| Trendelenburg/rev-trend | $\geq 15^\circ/\geq 25^\circ$   |
| Standard Accessory      | A pair of arm rods, a pair of leg support, a stainless steel sewage basin |
| Power Supply            | 220V 50Hz   |

**LABSTAC**

**Labstac LLC**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA  
Email: [contact@labstac.com](mailto:contact@labstac.com) | Website: [labstac.com](http://labstac.com)