

DUCTED FUME HOOD



DUCTED FUME HOOD

Created to provide protection from toxic fumes and hazardous volatile vapours, and are reliable and easy to use. Inbuilt ventilation system lowers the risk of fire and explosion. For metal analysis, pharmacy and research field along with safety measures, this product becomes unique choice for the buyers to purchase according to their needs.

Used in Commercial, Medical, Laboratory, Research Field.

Also known as Exhaust hoods, Laboratory Ducted fume hood.

FUH15-660 DUCTED FUME HOOD

Folding acrylic front window, down part with free stop function.

Microprocessor control system, LED display.

With memory function in case of power-failure.

Built-in centrifugal blower.

Interlock function: UV lamp and blower, LED lamp.(Only for choosing UV lamp)

Note: Experiments with strong acids and alkali, flammable or explosive substances cannot be conducted with this type fume hood.



SPECIFICATIONS

Model	FUH15-660
Air Velocity	0.3~0.8 m/s
Max Opening	660mm
Blower	Built-in centrifugal blower; Speed adjustable
Front Window	Folding acrylic window, down part with free stop function
Main Body Material	1.0mm cold-rolled steel with bacteria power coating
Work table material	Chemical resistant phenolic resin
Back&Side Windows Material	5mm toughened glass
LED Lamp	4Wx2
Standard Accessory	LED lamp, Active carbon filter, Blower, 4 meters PVC exhaust duct, Pipe strap
Optional Accessory	15W UV lamp, HEPA filter, Base stand
Noise	≤65dB
Internal Size (WxDxH)	640x550x700mm
External Size(WxDxH)	700x620x1150mm
Package Size with Base Stand(WxDxH)	840x960x1400mm
Package Size without Base Stand(WxDxH)	840x760x1400mm
Gross Weight with Base Stand	115kg
Gross Weight without Base Stand	100kg
Consumption	200 W
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@labstac.com | Website: labstac.com