

TURBIDITY METER



TURBIDITY METER

Used in Water treatment plants.

Also known as Turbidimeter.

MET71 TURBIDITY METER



SPECIFICATIONS

Model	MET71-200	MET71-240	MET71-232
Measuring Unit			
Range	(0 ~20.00) NTU, (20.0 ~200.0) NTU		(0.000 ~20.00) NTU, (20.01 ~200.0) NTU, (200 ~2000) NTU, (2001 ~4000) NTU
Resolution	0.01NTU, 0.1NTU, 1NTU	-	-
Accuracy	$\leq \pm 8 \%$	$\leq \pm 8\%$	$\leq \pm 6\%$
Fluctuation	$\leq \pm 1.0\% \text{ FS}/30 \text{ min}$	$\leq \pm 1.0 \%$ FS/30xmin	$\leq \pm 0.5 \%$ FS/30xmin
Repeatability	-	$\leq 1.0 \%$	$\leq 0.5 \%$
General			
Power Supply	AA Battery, AC Adapter 200-240 VAC input DC5V output	AC Adapter, 200-240 VAC input	
Dimension (mm) & Weight (kg)	100x220x80,0.8	330x250x130, 2.5	358x323x160, 8



MET71-200



MET71-240



MET71-232

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@labstac.com | Website: labstac.com