LABSTAC

DIGITAL DISPLAY ULTRASONIC CLEANER

labstac.com

DIGITAL DISPLAY ULTRASONIC CLEANER

Digital Display Ultrasonic Cleaner uses frequency of 40Khz for cleaning the lab equipments.
Used in Pharmaceutical,Chemical and physical cleaning, electronics industry, Research, laboraotory.
Also known as Digital ultrasonic cleaner, Ultrasonic cleaning bath, Ultrasonic cleaning tank.

ULC-13 DIGITAL DISPLAY ULTRASONIC CLEANER

Digital display and control

Industrial high Q transducers, cleaning conversion efficiency is higher

No stud- welding technology, Cleaning effect is better

MCU SWEEP multi frequency ultrasonic generator output, frequency sweep drive ultrasonic cleaning effect more powerful

MHC heating system, maximum temperature is up to 80℃

All stainless steel material inner tank is made by punching SUS304 1.0mm

2500V high voltage test to ensure the product safety, strict production, aging production quality control

SPECIFICATIONS

Model	ULC13-13	ULC13-2	ULC13-2A	ULC13-32
Capacity	1.3 L	2 L		3.2 L
Working frequency	40 Khz			
Ultrasonic Power	70 W			120 W
Heating power	No		100 W	
Timing time	10- 600s			1- 99 mins
Temperature range	No		0- 80℃	
Cover	Yes			
Drain valve	No			
Washing basket	Optional			
Inner tank dimension	150x135x65 mm	150x135x100 mm		240x135x100 mm
Packing size	242x227x265 mm		242x227x275 mm	342x240x310 mm
Gross weight	2.4 Kg	2.6 Kg	2.7 Kg	4.77 Kg
Power Supply	220V+ 10% 50Hz/60Hz 110V+ 10% 50Hz/60Hz			

Model	ULC13-50	ULC13-45	ULC13-68	ULC13-11
Capacity	5.0 L	4.5 L	6.8 L	11 L
Working frequency	40 Khz			
Ultrasonic Power	120 W	180 W		240 W
Heating power	200 W		300 W	400 W
Timing time	1- 99 mins			
Temperature range	0- 80℃			
Cover	Yes			
Drain valve	No			Yes
Washing basket	Optional			

Inner tank dimension	240x135x100 mm	300x150x100 mm	300x150x150 mm	300x240x150 mm
Packing size	342x240x355 mm	402x252x311 mm	402x252x355 mm	412x357x380 mm
Gross weight	5.4 Kg	5.65 Kg	6.2 Kg	8.5 Kg
Power Supply	220V+ 10% 50Hz/60Hz 110V+ 10% 50Hz/60Hz			

Model	ULC13-15	ULC13-20	ULC13-22	ULC13-30
Capacity	15 L	20 L	22 L	30 L
Working frequency	40 Khz			
Ultrasonic Power	360 W		480 W	600 W
Heating power	400 W/220V 400 W/110V		500 W/220V 500 W/110V	600 W/220V 500 W/110V
Timing time	1- 99 mins			
Temperature range	0- 80℃			
Cover	Yes			
Drain valve	Yes			
Washing basket	Optional			
Inner tank dimension	330x300x150 mm	330x300x200 mm	500x300x150 mm	500x300x200 mm
Packing size	472x437x470 mm		657x454x430 mm	657x450x475 mm
Gross weight	11.5 Kg	12.5 Kg	14.5 Kg	16.0 Kg
Power Supply	220V+ 10% 50Hz/60Hz 110V+ 10% 50Hz/60Hz			

ULC13-13

ULC13-2

ULC13-2A

ULC13-32

ULC13-50

ULC13-45

ULC13-68

ULC13-11

ULC13-15

ULC13-20

ULC13-22

ULC13-30

Labstac LLC
82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@labstac.com | Website: labstac.com