

HIGH FREQUENCY DESKTOP ULTRASONIC CLEANER



HIGH FREQUENCY DESKTOP ULTRASONIC CLEANER

High frequency ultrasonic cleaner is mainly used in medical industry, computers, microelectronics computers. It uses high frequency to clean the sub micron dirt without damaging the equipment

Used in Pharmaceutical, Chemical and physical cleaning, electronics industry, Research, laboratory.

Also known as Digital ultrasonic cleaner, Ultrasonic cleaning bath, Ultrasonic cleaning tank.

ULC-15 HIGH FREQUENCY DESKTOP ULTRASONIC CLEANER

Digital display and control ultrasonic power adjustable range from 0 to 100%

Special high frequency ultrasonic transducer (53/68/80/100/132 Khz)

No stud- welding technology, Cleaning effect is better

MCU SWEEP multi frequency ultrasonic generator output, frequency sweep drive ultrasonic cleaning effect more powerful

MHC heating system, maximum temperature is up to 80°C

All stainless steel material inner tank is made by punching SUS304 1.0mm

2500V high voltage test to ensure the product safety, strict production, aging production quality control



SPECIFICATIONS

Model	ULC15-32	ULC15-50	ULC15-45
Capacity	3.2 L	5.0 L	4.5 L
Working frequency	53/68/80 Khz		
Ultrasonic Power	120 W		180 W
Heating power	100 W	200 W	
Timing time	1- 99 mins		
Temperature range	0- 80°C		
Power regulation	No		
Drain valve	Yes		
Washing basket	Optional		
Inner tank dimension	240x135x100 mm	240x135x150 mm	300x150x100 mm
Packing size	342x240x355 mm	324x240x355 mm	300x150x100 mm
Gross weight	6.55 Kg	7.2 Kg	7.43 Kg
Power Supply	220V+ 10% 50Hz/60Hz 110V+ 10% 50Hz/60Hz		

Model	ULC15-68	ULC15-11	ULC15-15
Capacity	6.8 L	11 L	15 L
Working frequency	53/68/80 Khz	53/68/80/100/132 Khz	
Ultrasonic Power	180 W	240 W	360 W
Heating power	200 W	300 W	400 W/220V 400 W/110V
Timing time	1- 99 mins		

Temperature range	0- 80°C		
Power regulation	No	0-100 %	
Drain valve	Yes		
Washing basket	Optional		
Inner tank dimension	300x150x150 mm	300x240x150 mm	330x300x150 mm
Packing size	300x150x150 mm	300x240x150 mm	330x300x150 mm
Gross weight	8.0 Kg	8.5 kg	11.5 Kg
Power Supply	220V+ 10% 50Hz/60Hz 110V+ 10% 50Hz/60Hz		

Model	ULC15-20	ULC15-22	ULC15-30
Capacity	20 L	22 L	30 L
Working frequency	53/68/80/100/132 Khz		
Ultrasonic Power	360 W	480 W	600 W
Heating power	400 W/220V 400 W/110V	600 W/220V 500 W/110V	
Timing time	1- 99 mins		
Temperature range	0- 80°C		
Power regulation	0-100 %		
Drain valve	Yes		
Washing basket	Optional		
Inner tank dimension	330x300x200 mm	500x300x150 mm	500x300x200 mm
Packing size	330x300x200 mm	500x300x150 mm	500x300x200 mm
Gross weight	12.5 Kg	14.51 Kg	16 Kg
Power Supply	220V+ 10% 50Hz/60Hz 110V+ 10% 50Hz/60Hz		



ULC15-32



ULC15-50



ULC15-45



ULC15-68



ULC15-11



ULC15-15



ULC15-20



ULC15-22



ULC15-30

LABSTAC

Labstac LLC

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@labstac.com | Website: labstac.com