LABSTAC

CARBURETOR ULTRASONIC

labstac.com

CARBURETOR ULTRASONIC

Carburetor Ultrasonic Cleaner uses ultrasonic waves to clean the smallest part of the lab tool with strong degreasing chemical.

Used in Pharmaceutical,Chemical and physical cleaning, electronics industry, Research, laboraotory.

Also known as Digital ultrasonic cleaner, Ultrasonic cleaning bath, Ultrasonic cleaning tank.

ULC-16 CARBURETOR ULTRASONIC

- LCD display and control, simple operation
- One key degassing can quickly remove air in water and ultrasonic cleaning effect is better
- Independently developed MCU SWEEP ultrasonic generator drive, uniform and strong ultrasonic effect
- Independently developed industrial high Q value transducer with high ultrasonic conversion efficeincy and long service life
- Power adjustment function can meet different cleaning requirements
- Imported high strength glue Seedless nail bonding process, high ultrasonic conversion efficiency
- Digital timing cleaning time 10S-100 min and digital heating control temperature 20-80C arbitary settings
- The inner groove adopts imported SUS304, 1.0mm stainless steel stamping, ultrasonic exchanger effect is better effect is better and longer and service life
- The washing basket is made up of high quality 304 stainless steel mesh welding surface electrolyte polishing treatment
- The shell is made up of high quality stainless steel with better anti corrosion effect

SPECIFICATIONS

Model	ULC16-32	ULC16-50	ULC16-45
Capacity	3.2 L	5.0 L	4.5 L
Working frequency	39+ 1.5Khz		
Ultrasonic Power	120 W		180 W
Heating power	100 W	200 W	
Temperature range	20- 80℃		
Power regulation	0-100 %		
Drain valve	Yes		
Washing basket	Optional		
Cover	Yes		
Degas	Yes		
Inner tank dimension	240x135x100 mm	240x135x150 mm	300x150x100 mm
Packing size	342x240x355 mm		402x252x355 mm
Gross weight	4.77 Kg	5.4 Kg	5.65 Kg
Power Supply	220V+ 10% 50Hz/60Hz 110V+ 10% 50Hz/60Hz		

Model	ULC16-68	ULC16-11	ULC16-15
Capacity	6.8 L	11 L	15 L
Working frequency	39+ 1.5Khz		

Ultrasonic Power	180 W	240 W	360 W
Heating power	200 W	300 W	400 W
Temperature range	20- 80℃		
Power regulation	0-100 %		
Drain valve	Yes		
Washing basket	Optional		
Cover	Yes		
Degas	Yes		
Inner tank dimension	300x150x150 mm	300x240x150 mm	330x300x150 mm
Packing size	402x252x355 mm	412x357x380 mm	472x437x420 mm
Gross weight	6.2 Kg	8.5 Kg	11.5 Kg
Power Supply	220V+ 10% 50Hz/60Hz 110V+ 10% 50Hz/60Hz		

Model	ULC16-20	ULC16-22	ULC16-30
Capacity	20 L	22 L	30 L
Working frequency	39+ 1.5Khz		
Ultrasonic Power	360 W	480 W	600 W
Heating power	400 W	500 W	600 W/220V 500 W/110V
Temperature range	20- 80℃		
Power regulation	0-100 %		
Drain valve	Yes		
Washing basket	Optional		
Cover	Yes		
Degas	Yes		
Inner tank dimension	330x300x200 mm	500x300x150 mm	500x300x200 mm
Packing size	472x437x470 mm	675x454x430 mm	657x450x475 mm
Gross weight	12.5 Kg	14.5 Kg	16.0 Kg
Power Supply	220V+ 10% 50Hz/60Hz 110V+ 10% 50Hz/60Hz		

ULC16-32

ULC16-50

ULC16-45

ULC16-68

ULC16-11

ULC16-15

ULC16-20

ULC16-22

ULC16-30

Labstac LLC
82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: contact@mail.labstac.com | Website: labstac.com